

Nordstrom Contracting
 Consulting Corp
 36 Theills Mt Ivy Rd
 Pomona, NY 10970

LETTER OF TRANSMITTAL

Project 561A4-15-102
 Lyons VA - Correct FCA
 Deficiencies Bld 1

To: Mr. Gary Bohner

General Engineer
 Montrose Campus
 151 Knollcroft Rd
 Lyons, NJ 07939

Submittal # _____

We are sending you Herewith Delivered by Hand Under Separate Cover Via ELECTRONIC

Plans Prints Shop Dwgs Samples Specifications Other _____

Copies	Item	# Pages	Description
			Division 079200- Joint Sealants
1	1	3	DAP Alex Plus- All-purpose Acrylic Latex silicone caulk
1	2	3	DAP- Silicone Plus- Waterproof Silicone- Kitchen & Bath Caulk
1	3	3	DAP- Alex Flex- Molding and Trim Caulk
1	4	30	DAP- Catalog- Various caulks & sealants- TBD By Application
1	5		
1	6		
1	7		
1	8		
1	9		
1	10		

The Above Listed Items are transmitted as indicted below:

Return By Date: SEE BAR CHART

_____ Approved

_____ Approved with corrections as noted on submittal data and/or attached sheets (s)

Signature: _____

Title: _____

Date: _____

Remarks: _____



Technical Bulletin

2400 Boston Street, Suite 200, Baltimore, Maryland 21224
Phone: 410-675-2100 or 800-543-3840

Revised: 2/12/15

DAP[®] ALEX PLUS[®] Acrylic Latex Adhesive Caulk Plus Silicone

- **Waterproof Seal**
- **Paintable**
- **Cured Caulk is Mold & Mildew Resistant**
- **Excellent Flexibility**
- **Easy Water Clean-Up**
- **Indoor/Outdoor Use**
- **Exceeds ASTM C834**

Packaging: 10.1 fluid ounce (300 mL) cartridge, 11.2 fluid ounce (331 mL), 5.5 fluid ounce (162 mL) squeeze tube

Colors: White

UPC Numbers: 70798 18101, 70798 18136, 70798 18155, 70798 18128, 70798 11440, 70798 18101

Company Identification:

Manufacturer: DAP Inc., 2400 Boston St., Baltimore, Maryland 21224

Usage Information: Call 1-888-DAP-TIPS or visit dap.com & click on “Ask the Expert”

Order Information: 800-327-3339

Fax Number: 410-534-2650

Product Description:

ALEX PLUS[®] Acrylic Latex Caulk Plus Silicone is a professional quality caulking product formulated to last. It is an all-purpose adhesive caulk ideal for a wide variety of applications for interior and exterior use. ALEX PLUS[®] contains silicone, which allows for excellent adhesion and flexibility to resist expansion and contraction without cracking. It provides a waterproof seal and prevents air and moisture from passing through cracks and joints thereby improving energy efficiency. Cured caulk is mildew resistant. ALEX PLUS[®] is paintable with latex and oil-based paints. It is easy to use, easy to tool, low in odor, cleans up easily with soap and water and has a low VOC content.

Suggested Uses:

Ideal for caulking and sealing:

- *Window & door frames*
- *Eaves*
- *Baseboards*
- *Pipes*
- *Molding*
- *Vents*
- *Siding and trim*
- *Corner Joints*
- *Ducts*

Adheres To:

- Wood
- Brick
- Drywall
- Metal
- Painted Surfaces
- Glass
- Plaster
- Most common building materials

Performance Characteristics:

- Exceeds ASTM C834.
- Contains silicone to improve adhesion and flexibility.
- Resists cracking and chalking.
- Tack-free in 30 minutes.

Surface Preparation & Application:

1. Surface must be clean, dry and free of all old caulk, dirt, dust, grease and debris.
2. Remove cap (from tube). Cut nozzle at 45° angle to desired bead size.
3. Load into caulking gun if using the 10.1 oz. cartridge.
4. Fill gap with caulk, pushing caulk ahead of nozzle.
5. For a neat finish, smooth the bead of caulk with a finishing tool.
6. Clean up excess caulk with a damp sponge before it skins over.
7. Allow caulk to dry at 30 minutes (longer in cool or humid conditions) before painting with latex or oil-based paints.
8. Reseal for storage and reuse.

For Best Results:

- Caulk in temperatures above 40°F.
- Do not apply when rain or freezing temperatures are forecasted before full cure can occur. Cold weather and high humidity will slow down cure time.
- Do not use below waterline or for marine or automobile applications.
- Do not use for filling butt joints, surface defects or for tuck-pointing.
- Joint size should not exceed 1/2" wide x 1/2" deep. If joint depth exceeds 1/2", use backer rod material.
- Store caulk away from extreme heat or cold.

Typical Physical & Chemical Characteristics:

Vehicle:	Siliconized Acrylic Polymer
Volatile:	Water
Solids:	83% by weight
Weight per Gallon:	14.0 lbs./gal.
Service Temperature:	-20°F to 180°F
Temperature Application Range:	40°F to 100°F
Freeze Thaw Stability:	Passes 5 Cycles @ 0°C (1 cycle = 16 hrs. @ 0°C, 8 hrs. @ 25° C)
Dynamic Joint Movement:	± 12%
Flash Point:	None
Consistency:	Smooth and creamy
Applications:	Interior/Exterior
Shelf Life:	1 Year
Coverage:	10.1 fl. oz.: 55 linear feet at a 3/16" diameter bead 5.5 fl. oz.: 30 linear feet at 3/16" diameter bead
Odor:	Very mild
Tooling Time:	10 minutes
Tack Free Time:	30 minutes
SDS No:	10002

Clean Up:

Clean up excess uncured caulk with a damp sponge before it skins over. Wash hands with warm water and soap. Dried material must be cut or scraped away.

Safety:

See product label or Safety Data Sheet for safety information. You can request an SDS sheet by calling 888-DAP-TIPS or by visiting our website at www.dap.com.

Guarantee:

If product fails to perform when used as directed, within one year of date of purchase, return used container & sales receipt to DAP Products Inc., Technical Customer Service, 2400 Boston St., Ste. 200, Baltimore, MD 21224 for replacement product or sales price refund. DAP is not liable for incidental or consequential damages.



Technical Bulletin

2400 Boston Street, Suite 200, Baltimore, Maryland 21224
Phone: 410-675-2100 or 800-543-3840

Revised: January 30, 2014

DAP[®] Silicone *Plus*[™] Premium Silicone Rubber Kitchen & Bath Sealant

- Water resistant in 30 minutes
- Cured Sealant is Mildew Resistant
- No Cracking or Shrinking
- Low Odor
- Superior Flexibility and Adhesion
- ASTM C 920, CLASS 25, TYPE S, GRADE NS
- Lifetime Guarantee

Packaging: 10.8 fluid ounce cartridges (319 ml), 2.8 fluid ounce squeeze tube (83 ml)
Colors: White, Almond, Clear
UPC Number: 0 70798 08770 5, 0 70798 08785 9, 0 70798 08781 1, 0 70798 73376 3, 0 70798 73380 0,
0 70798 73382 4

Company Identification:

Manufactured For: DAP Products Inc., 2400 Boston St., Suite 200, Baltimore, Maryland 21224
Usage Information: DAP HELPLINE: 888-DAP-TIPS, 9:00 am to 7:00 pm EST.
Order Information: 800-327-3339
Fax Number: 410-534-2650
Also, visit the DAP website at www.dap.com.

Product Description:

DAP[®] Silicone *Plus*[™] Premium Silicone Rubber Kitchen & Bath Sealant is a one-component neutral cure material that cures to a tough rubbery solid upon exposure to moisture in the air. It provides a long lasting, flexible, watertight seal and offers excellent adhesion for kitchen and bath applications. Backed by a Lifetime Guarantee.

Suggested Uses:

Ideal for Caulking and Sealing:

- Showers
- Tubs
- Toilets
- Sinks
- Backsplashes
- Countertops
- Fixtures
- Repairing loose tiles
- Filling and sealing cracks and joints

Adheres to:

- Plastic
- Ceramic/tile
- Glass
- Porcelain
- Cultured Marble
- Vinyl
- Fiberglass
- Metal

- Wood

- Drywall/Plaster

Surface Preparation & Application:

1. Surface must be clean, dry and free of old caulk, dirt and debris.
2. Cut nozzle at 45° angle to desired bead size.
3. Puncture inner foil seal.
4. Load cartridge into caulking gun.
5. Fill gap with sealant, pushing sealant ahead of nozzle.
6. If necessary, smooth bead with a finishing tool.
7. 73°F and 50% relative humidity, sealant is water resistant 30 minutes after application and reaches full cure in 24 hours. Low humidity may slow cure.
8. Clean up excess uncured sealant with mineral spirits. Scrape or cut away excess cured sealant. Do not use mineral spirit to clean skin.

For Best Results:

- Not recommended for filling butt joints, surface defects, tuck-pointing, stovepipes, chimneys, fireplace applications, continuous underwater use or on oily woods and some metals.
- Joint width should not exceed 1/2". If joint depth exceeds 1/2", use polyethylene foam as backup filler.
- Not recommended for structural glazing.
- Not paintable. Paint substrate surface before applying sealant.
- Store below 90°F in a dry place for optimal shelf life.
- Not recommended on surfaces that might bleed oils, plasticizers or solvents. Best adhesion and compatibility are not achieved with substrates made of methacrylate, polycarbonate, polypropylene, polyethylene or polytetrafluoroethylene. Evaluate such substrates before using sealant.
- Allow 24 hours for sealant to cure. Sealant will not cure in totally confined spaces.

Typical Physical & Chemical Characteristics:

Base:	Silicone
Solids:	> 97.0% by weight
Weight per Gallon:	8.7 lbs./gal.
Temperature Service Range:	-40°F to 300°F
Temperature Application Range:	40°F to 120°F
Consistency:	Smooth Paste
Open or Tooling Time:	10-15 Minutes
Tack-free time	<60 minutes
Cleanup:	Mineral Spirits (when uncured)
Shelf Life:	18 Months from manufacturing date
Coverage 10.8 fl. oz cartridge	59 linear feet at 3/16" diameter bead
2.8 fl. oz. squeeze tube	15 linear feet at 3/16" diameter bead
70798 08770 SDS No.:	000 08770 001
70798 73376 SDS No.:	000 73376 605
70798 08785 SDS No.:	000 08785 001
70798 73380 SDS No.:	000 73380 605
70798 08781 SDS No.:	000 08781 001
70798 73382 SDS No.:	000 73382 605

Clean Up:

Before curing, remove excess material with a solvent-moistened towel. After product has cured, material must be cut or scraped away. Clean tools with mineral spirits. Do not use mineral spirit to clean skin.

Safety:

WARNING! VAPOR HARMFUL. MAY CAUSE ALLERGIC SKIN REACTION. Methylcelketoxime is evolved during cure. May cause eye, skin and respiratory irritation. May cause drowsiness. Repeated or prolonged exposure may cause adverse skin, blood & liver effects. Harmful if swallowed or absorbed through the skin. Do not breathe vapors. Use only with adequate ventilation. Ensure fresh air entry during application and drying. Avoid contact with eyes and skin. Wear gloves and safety glasses. Wash thoroughly after handling. **WARNING:** This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. **FIRST AID:** SKIN: Wash thoroughly. EYE: immediately flood with plenty of water. INHALATION: Remove to fresh air. INGESTION: DO NOT INDUCE VOMITING. Get medical attention if complications arise from any exposure. **For emergencies**, call your poison control center at 1-800-222-1222. See product label and Safety Data Sheet (SDS) for additional information. For an SDS, contact your supplier or visit dap.com. **KEEP OUT OF REACH OF CHILDREN. DO NOT TAKE INTERNALLY.**

Lifetime Guarantee:

DAP warrants the performance of this product for sealant purposes during the lifetime of your home. If not satisfied, return used container and sales receipt to DAP Products Inc., Technical Customer Service, 2400 Boston Street, Suite 200, Baltimore, MD 21224 for product replacement or sales price refund. DAP will not be liable for incidental or consequential damages.



Technical Bulletin

2400 Boston Street, Suite 200, Baltimore, Maryland 21224
Phone: 410-675-2100 or 800-543-3840

Revised: 2/12/15

DAP® ALEX FLEX™ Premium Molding & Trim Sealant - White

- Exceeds ASTM C920, Class 12.5
- Crack proof
- Maximum flexibility and adhesion
- Outstanding paintability in 30 Minutes
- Won't shine through paint
- Cured sealant is mold and mildew resistant
- Easy water clean-up
- Waterproof seal
- Ideal for wood and PVC molding

Packaging: 10.1 fl. oz. (300 mL) cartridge
Color: White
UPC Number: 7079818542, 7079818542, 7079811442

Company Identification:

Manufacturer: DAP Products Inc., 2400 Boston St., Ste. 200, Baltimore, Maryland 21224
Usage Information: Call 1-888-DAP-TIPS or visit dap.com & click on "Ask the Expert"
Order Information: 800-327-3339
Fax Number: 410-534-2650

Product Description:

DAP® ALEX FLEX™ PREMIUM MOLDING & TRIM SEALANT is specifically formulated for use on molding & trim applications. It delivers maximum adhesion & flexibility for a crack proof seal. It provides easy tooling, low odor, water clean-up & outstanding paintability. In just 30 minutes, the sealant forms a tough outer skin that's dry enough to paint over with latex or oil based paints, thereby saving time since the job is finished faster. It provides a long-lasting, durable seal that will not shine through paint. Ideal for achieving a professional look with paint projects when sealing gaps around windows, doors, trim, crown molding, chair rails and baseboards. Cured sealant is mold and mildew resistant. Indoor use. Exceeds ASTM Specification C920, Class 12.5.

Suggested Uses:

Ideal for Caulking and Sealing:

- | | | |
|--|--|--|
| <input type="checkbox"/> Windows and doors | <input type="checkbox"/> Crown molding | <input type="checkbox"/> Chair rails |
| <input type="checkbox"/> Molding | <input type="checkbox"/> Trim | <input type="checkbox"/> Vents |
| <input type="checkbox"/> Baseboards | <input type="checkbox"/> Corner joints | <input type="checkbox"/> Other gaps and cracks |

Outstanding Adhesion to:

- | | | |
|--|---|--|
| <input type="checkbox"/> Wood | <input type="checkbox"/> Metal | <input type="checkbox"/> Brick |
| <input type="checkbox"/> Aluminum | <input type="checkbox"/> Glass | <input type="checkbox"/> Concrete |
| <input type="checkbox"/> Vinyl | <input type="checkbox"/> Masonry | <input type="checkbox"/> Most plastics |
| <input type="checkbox"/> Plaster and drywall | <input type="checkbox"/> Stucco | <input type="checkbox"/> Stone |
| <input type="checkbox"/> Painted surfaces | <input type="checkbox"/> Composite Wood | <input type="checkbox"/> PVC Molding |

Performance Characteristics:

- Exceeds the requirements of ASTM C920 standard specification for Elastomeric joint sealants, Type S, Grade NS, Class 12.5. Use NT, G, A and M.
- Exceeds ASTM Spec C834 Standard Specification for Latex Sealants.
- Paintable in 30 minutes with latex or oil-based paints
- Tack free in 15 minutes.
- Easy water clean-up.

Surface Preparation & Application:

1. Surface must be clean, dry and free of old sealant, dirt, dust, debris and grease.
2. Trim the nozzle at 45° angle to desired bead size and load cartridge into caulking gun.
3. Fill the gap with sealant, pushing sealant ahead of nozzle.
4. If necessary, smooth or tool the bead with a finishing tool.
5. Clean up excess uncured sealant with a damp sponge before it skins over. Cured sealant must be cut or scraped away.
6. Allow 30 minutes for skin to form prior to painting. Allow additional dry time in high humidity or cool temperatures. Allow 72 hours for sealant to cure completely.
7. Reseal cartridge for storage and reuse.

For Best Results:

- Apply in temperatures above 40°F (4.44 °C).
- Do not apply if rain or freezing temperatures are forecasted or before full cure can occur. Cold weather and/or high humidity will slow down cure time.
- Do not use below waterline or for marine or automobile applications, or filling surface defects.
- Joint size should not exceed 1/2" (1.30 cm) wide by 1/2" (1.30 cm) deep. If joint depth exceeds 1/2" (1.30 cm), use foam backer rod.
- Store sealant away from extreme heat or cold.

Typical Physical & Chemical Characteristics:

Tooling Time:	10 Minutes
Tack-Free Time:	15 Minutes
Dynamic Joint Movement:	± 12.5%
Paintable:	Yes
Odor:	Very Mild
Consistency:	Smooth and Creamy
Vehicle:	Advanced Acrylic Polymer
Volatile:	Water
Flash Point:	> 212°F
Filler:	Calcium Carbonate
Density:	1.52
Solids:	80.0% by weight
Weight per Gallon:	12.7 lbs./gal. (1.49 kg/L)

Typical Physical & Chemical Characteristics (Continued):

Temperature Service Range:	-30°F to 180°F (- 34.50 to 82.20 °C)
Temperature Application Range:	40°F to 100°F (4.44 to 37.78 ° C)
Freeze Thaw Stability:	Passes 5 Cycles 0°F (- 17.78 °C)
Shelf Life:	12 Months
Coverage:	55 linear ft. at a 3/16" bead size. (16.76 m at a 0.47 cm bead size)
SDS No:	00010124001

Clean Up:

Clean up excess uncured sealant with a damp cloth or sponge before it skins over. Wash hands with warm water and soap. Dried material must be cut or scraped away.

Safety:

See product label or Safety Data Sheet for safety information. You can request an SDS sheet by calling 888-DAP-TIPS or by visiting our website at www.dap.com.

Guarantee:

If product fails to perform when used as directed, within one year of date of purchase, return used container & sales receipt to DAP Products Inc., Technical Customer Service, 2400 Boston St., Ste. 200, Baltimore, MD 21224 for replacement product or sales price refund. DAP is not liable for incidental or consequential damages.



You'll find us in all the right places.®



General Information

Minimum order requirement is \$250.
Each product is identified by size and color with a case code number. Please use this number when ordering.

Order Codes

DAP manufacturer's code No: 70798

Customer Service Information

Call our Customer Service Department for assistance on order placement, deliveries, billing inquiries and authorization to return materials.

Mail correspondence and confirming purchase orders to:

DAP Products Inc.
2400 Boston Street, Suite 200
Baltimore, MD 21224
Fax order to: 410-558-1068
E-mail order to: orders@dap.com

Customer Service Department

800-DAP-3339
410-675-2100
(8:00 a.m. – 6:00 p.m. Eastern Time)

International Customer Service

800-323-0645
(8:00 a.m. – 6:00 p.m. Eastern Time)

Technical Customer Service

888-327-8477 or 888-DAP-TIPS
(8:00 a.m. – 6:00 p.m. Eastern Time)

Corporate Office

800-543-3840
410-675-2100

Supplemental Price Lists

For a copy of a current price list and conditions of sale, please contact your sales representative.

SDS Requests

To obtain an SDS for any DAP product, please visit our website www.dap.com or call 888-DAP-TIPS.

Reduce Environmental Impact by Choosing Low VOC Content Products



DAP is dedicated to the development of adhesives and sealants with low volatile organic compound (VOC) content. Many of our products actually have a low enough VOC content, indicated by this symbol, to meet one or more of the guidelines outlined below:

- The South Coast Air Quality Management District (SCAQMD) Rule # 1168
- The Bay Area Air Quality Management District Regulation 8, Rule 51
- U.S. Green Building Council® LEED® - NC Green Building Rating System for New Construction & Major Renovations Version 2.2, EQ Credit 4.1 (Indoor Environmental Quality – Low Emitting Materials: Adhesives & Sealants)
- NAHB Model GREEN Home Building Guideline Section 7.1.3 (Global Impact - Products)

Increase Energy Efficiency by Sealing the Building Envelope



In order to meet green building guidelines for energy efficiency you will need to take an integrated and comprehensive approach to an energy efficient design of the building site, the building envelope and mechanical space conditioning systems. Utilize products highlighted with this symbol when sealing the building envelope in accordance with the following guidelines:

- U.S. Green Building Council® LEED® - NC Green Building Rating System for New Construction and Major Renovations Version 2.2, EA Prerequisite 2 for Minimum Energy Performance. (Energy & Atmosphere – Minimum Energy Performance)
- NAHB Model GREEN Home Building Guidelines Section 3.3.1 Building Envelope (PP) B. (Energy Efficiency – Implement an Integrated and Comprehensive Approach to Energy – Efficient Design of Building Site, Building Envelope and Mechanical Space Conditioning Systems)
- ANSI/ASHRAE/IESNA Standard 90.1-2004 – Energy Standard for Buildings Except Low Rise Residential Buildings SI Edition – Section 5.4 and 5.5 (Building Envelope)



Retail Product Guide

Table of Contents

DAP® Caulks & Sealants 1-17

- Indoor/Outdoor Sealants 1**
- Kitchen/Bath Sealants. 5**
- Specialty Sealants. 6**
- Specialty Sealants - Fire System Sealants. 9**
- Insulating Foam Sealants 10**
- Indoor/Outdoor Advanced Sealants & Silicones 11**
- Kitchen/Bath Advanced Sealants & Silicones 12**
- Specialty Advanced Sealants & Silicones 14**
- Accessories 17**

DAP® Repair Products 18-34

- Spackling Compounds 18**
- Glazing Compounds 22**
- Wood Repair Products 23**
- Concrete & Masonry Products 26**
- Joint Compounds 29**
- Plasters & Stuccos 30**
- Miscellaneous Products 33**

DAP® Construction Adhesives 35-52

- Contact Cements 35**
- Industrial Contact Cements 36**
- Specialty Adhesives 37**
- SmartBond® Construction Adhesives. 40**
- Cartridge & Canned Construction Adhesives 43**
- VOC-Compliant Construction Adhesives 46**
- Floor Covering Adhesives 50**



DAP® ALEX PLUS® Acrylic Latex Caulk Plus Silicone



Superior quality, all-purpose acrylic latex caulk plus silicone. Highly flexible and durable for a waterproof seal. Excellent adhesion. Cured caulk is mold and mildew resistant. Easy to apply and tool. Paintable. Easy water clean-up. Interior/exterior use. Exceeds ASTM Specification C834.



Table with 10 columns: Case Code, Size, Color, Product Code, Case Weight (lbs.), Case Pack, Case Dimensions LxWxH, Case Volume (cu.ft.), UPC Check Digit, Cases per Pallet. Lists various product variants like 18128, 18129, 18152, etc.

DAP® ALEX PLUS® Acrylic Latex Caulk Plus Silicone Contractor Pack



Buy by the case and save! Designed for purchase by the case by professional contractors. Each pack contains 12 cartridges of ALEX PLUS® Acrylic Latex Caulk Plus Silicone.



Table with 10 columns: Case Code, Size, Color, Product Code, Case Weight (lbs.), Case Pack, Case Dimensions LxWxH, Case Volume (cu.ft.), UPC Check Digit, Cases per Pallet. Lists contractor pack variants like 18656, 18660.

DAP® ALEX PLUS® Easy Caulk Acrylic Latex Caulk Plus Silicone



ALEX PLUS® formula in a convenient, easy-to-use aerosol can. NO CAULK GUN NEEDED! Gives perfect control for a smooth, consistent bead with no messy overflow. Ideal for use in tight spaces and for smaller jobs. Interior/exterior use.



Table with 10 columns: Case Code, Size, Color, Product Code, Case Weight (lbs.), Case Pack, Case Dimensions LxWxH, Case Volume (cu.ft.), UPC Check Digit, Cases per Pallet. Lists easy caulk variant 18736.



DAP® ALEX Fast Dry® Acrylic Latex Caulk Plus Silicone

Ready to paint in 30 minutes so you can finish the job faster. This durable, flexible caulk won't crack paint. Cured caulk is mold and mildew resistant. Easy to apply and tool. Provides a waterproof seal with excellent adhesion. Easy water clean-up. Interior/exterior use. Exceeds ASTM Specification C834.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
18425	10.1 OZ	WHITE	18425	14.75	12	8"x6"x12"	0.33	1	108
18405	5.5 OZ	WHITE	11425	8.00	12	9.5"x7.25"x4.25"	0.17	8	240

DAP® ALEX Fast Dry® Acrylic Latex Caulk Plus Silicone Contractor Pack

Buy by the case and save! Designed for purchase by the case by professional contractors. Each pack contains 12 cartridges of ALEX Fast Dry® Acrylic Latex Caulk Plus Silicone.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
18426	10.1 OZ	WHITE	18425	14.75	12	8"x6"x12"	0.33	1	108

DAP® DYNAFLEX 230® Premium Indoor/Outdoor Sealant

DAP® DYNAFLEX 230® delivers a "Silicone Tough" latex formulation for outstanding exterior performance against the elements. Developed for flexibility and crack proof performance, this sealant endures expansion and contraction without cracking or losing its seal. The paintable, durable sealant can fill gaps up to 1" wide and the cured sealant is mold and mildew resistant. It has excellent adhesion to a wide range of building materials including wood, MDF, PVC, polystyrene, and composite trimboard. Easy to gun out, tools smoothly and can be cleaned up with soap and water. Interior/exterior use. Meets ASTM Specification C920, Class 25.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
18275	10.1 OZ	WHITE	18300	13.10	12	8"x6"x12"	0.33	1	108
18885	5.5 OZ	WHITE	18285	12.01	20	9.75"x7.75"x9.88"	0.43	1	96
18304	10.1 OZ	CLEAR	18305	10.01	12	8"x6"x12"	0.33	6	108
18857	5.5 OZ	CLEAR	18357	8.83	20	9.75"x7.75"x9.88"	0.43	5	96
18288	10.1 OZ	ALMOND	18306	12.85	12	8"x6"x12"	0.33	3	108
18286	10.1 OZ	GRAY	18301	12.85	12	8"x6"x12"	0.33	8	108
18416	10.1 OZ	CLAY	18416	13.00	12	8"x6"x12"	0.33	9	108
18280	10.1 OZ	BLACK	18280	12.80	12	8"x6"x12"	0.33	6	108
18418	10.1 OZ	BROWN	18302	12.90	12	8"x6"x12"	0.33	5	108
18412	10.1 OZ	CEDAR TAN	18412	12.90	12	8"x6"x12"	0.33	1	108
18420	10.1 OZ	DARK BRONZE	18303	12.90	12	8"x6"x12"	0.33	2	108



DAP® ALEX FLEX™ Premium Molding & Trim Sealant

DAP® ALEX FLEX™ Premium Molding & Trim Sealant is specifically formulated for use on molding and trim applications. It delivers maximum adhesion and flexibility for a crack proof seal. It provides easy tooling, low odor, water clean-up and outstanding paintability. In just 30 minutes, the sealant forms a tough outer skin that's dry enough to paint over with latex or oil-based paints, thereby saving time since the job is finished faster. It provides a long-lasting, durable seal that will not shine through paint. Ideal for achieving a professional look with paint projects when sealing gaps around windows, doors, trim, crown molding, chair rails and baseboards. Cured sealant is mold and mildew resistant. Interior/exterior use. Exceeds ASTM Specification C920, Class 12.5.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
18542	10.1 OZ	WHITE	18542	13.64	12	8"x6"x12"	0.33	5	108

DAP® SIMPLE SEAL™ Paint Projects Easy-to-Use Home Sealant

DAP® SIMPLE SEAL™ Paint Projects Sealant is an easy way to achieve professional-looking results by sealing gaps and cracks around trim, molding and baseboards prior to painting. NO CAULK GUN NEEDED! Simply press and seal to dispense an even bead of caulk. Compact design fits in the palm of the hand to easily navigate tight spaces and corners. SIMPLE SEAL™ dries fast and is ready to paint in only 30 minutes to save time. Cured sealant is mold and mildew resistant. Low odor. Cleans up easily with water. Interior/exterior use.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
18774	9 OZ	WHITE	18774	6.64	9	8.75"x8.75"x7.50"	0.33	0	140

DAP® SIMPLE SEAL™ Weatherproofing Easy-to-Use Home Sealant

DAP® SIMPLE SEAL™ Weatherproofing Sealant is an easy way to seal out drafts and moisture around windows, doors, baseboards, inside or outside of the home to save energy and improve comfort. NO CAULK GUN NEEDED! Simply press and seal to dispense an even bead of caulk. Compact design fits in the palm of the hand to easily navigate tight spaces and corners. Use SIMPLE SEAL™ to seal out air leaks and moisture to improve the energy efficiency of the home and make it more comfortable. Cured sealant is mold and mildew resistant. Low odor and paintable. Cleans up easily with water. Interior/exterior use.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
18773	9 OZ	WHITE	18773	6.64	9	8.75"x8.75"x7.50"	0.33	3	140



**DAP® ALEX®
Painter's Acrylic
Latex Caulk**

All-purpose acrylic latex painter's caulk. Applies smoothly and easily. Adheres to wood, plaster, drywall and masonry. Resists cracking and chalking. Paintable. Easy water clean-up. Interior/exterior use. Meets ASTM Specification C834 for extrudability, artificial weathering, extension-recovery and slump.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
18670	10.1 OZ	WHITE	18065	14.40	12	8"x6"x12"	0.33	9	108
18609	10.1 OZ	WHITE	18065	35.80	30	12"x10"x12"	0.83	9	48

**DAP® ALEX®
Painter's Acrylic
Latex Caulk
Contractor Pack**

Buy by the case and save! Designed for purchase by the case by professional contractors. Each pack contains 12 cartridges of ALEX® Painter's Acrylic Latex Caulk.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
18618	10.1 OZ	WHITE	18065	14.40	12	8"x6"x12"	0.33	9	108

**DAP® RELY-ON®
Latex Caulk**

Economical latex for general caulking purposes. Paintable. Easy water clean-up.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
18260	10.1 OZ	WHITE	18250	14.40	12	8"x6"x12"	0.33	9	108



DAP® KWIK SEAL PLUS® Premium Kitchen & Bath Adhesive Sealant with MICROBAN® Antimicrobial Product Protection

Premium adhesive sealant with MICROBAN® Antimicrobial Product Protection fights the growth of stain and odor-causing bacteria, mold and mildew on the sealant. Specially formulated siliconized latex provides maximum adhesion and flexibility for a durable, waterproof seal. Paintable. Easy water clean-up. Low odor. Backed by a Crack-Proof Guarantee.



Table with 10 columns: Case Code, Size, Color, Product Code, Case Weight (lbs.), Case Pack, Case Dimensions LxWxH, Case Volume (cu.ft.), UPC Check Digit, Cases per Pallet. Rows include product codes 18546 through 18519.

DAP® KWIK SEAL® Kitchen & Bath Adhesive Caulk

Bonds like a glue and seals like a caulk. Provides a durable, waterproof seal. Excellent adhesion. Tools easily. Cured caulk is mold and mildew resistant. Paintable. Easy water clean-up.



Table with 10 columns: Case Code, Size, Color, Product Code, Case Weight (lbs.), Case Pack, Case Dimensions LxWxH, Case Volume (cu.ft.), UPC Check Digit, Cases per Pallet. Rows include product codes 18001 through 18242.

DAP® SIMPLE SEAL™ Kitchen & Bath Easy-to-Use Home Sealant

DAP® SIMPLE SEAL™ Kitchen & Bath Sealant is an easy way to fill and seal gaps around tubs, sinks, showers, counter tops or anywhere a clean, waterproof seal is needed in kitchens and bathrooms. NO CAULK GUN NEEDED! Simply press and seal to dispense an even bead of caulk. Compact design fits in the palm of the hand to easily navigate tight spaces and corners. Use SIMPLE SEAL™ to seal out water and moisture or replace stained or mildewed caulk. Cured sealant is mold and mildew resistant. Low odor and paintable. Cleans up easily with water.



Table with 10 columns: Case Code, Size, Color, Product Code, Case Weight (lbs.), Case Pack, Case Dimensions LxWxH, Case Volume (cu.ft.), UPC Check Digit, Cases per Pallet. Row includes product code 18772.



DAP® Premium Polyurethane Adhesive Sealant

One-part, moisture-curing, non-sag elastomeric commercial-grade sealant specifically formulated to provide a long-lasting, durable seal when filling exterior gaps, joints and cracks. This high-performance sealant offers superior adhesion to most substrates and remains flexible to withstand up to ±35% joint movement when installed into a properly prepared joint. Exceptional cut and tear resistance. Handles foot and vehicle traffic. Paintable. Interior/exterior use. Meets or exceeds ASTM C920, Type S, Grade NS, Class 35. NSF/ANSI Standard 61. Use T, NT, O, M, I. CAN/CGSB 19.13-M87 and Federal Specification TT-S-00230C, Type II, Class A.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
18810	10.1 OZ	WHITE	18810	14.10	12	8"x6"x13"	0.36	5	132
18816	10.1 OZ	BLACK	18816	14.10	12	8"x6"x13"	0.36	7	132
18814	10.1 OZ	GRAY	18814	14.50	12	8"x6"x13"	0.36	3	132

DAP® BUTYL-FLEX® Gutter & Flashing Sealant

Butyl rubber formula provides a durable, flexible and waterproof seal for gutters, drainspouts, lap joints, flashings, roof vents, aluminum siding and other metal joints. Stands up to weather and temperature extremes. Meets ASTM Specification C1085. Exterior use.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
18182	10.1 OZ	WHITE	18184	13.75	12	8"x6"x12"	0.33	7	108
18188	10.1 OZ	ALUMINUM GRAY	18185	13.75	12	8"x6"x12"	0.33	4	108

DAP® BUTYL-FLEX® Gutter & Flashing VOC-Compliant Adhesive

Butyl rubber-based, lower solvent formula provides a durable, flexible and waterproof bond for gutters, drainspouts, lap joints, flashing, roof vents, aluminum siding and other metal joints. Stands up to weather and temperature extremes. Exterior use.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
27062	10.1 OZ	WHITE	27062	13.75	12	8"x6"x12"	0.33	6	108



DAP® Concrete & Masonry Filler & Sealant

High performance, latex-based sealant formulated to repair cracks and holes in concrete, mortar and masonry. Contains silicone additives for improved adhesion and water resistance. Forms a durable, flexible and waterproof seal. Resists gas, oil, grease and salt. Paintable. Easy water clean-up. Interior/exterior use.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
18096	10.1 OZ	GRAY	18021	14.87	12	8"x6"x12"	0.33	5	108

DAP® Blacktop Asphalt Filler & Sealer

High performance, asphalt-based compound for filling and sealing cracks in driveways, parking lots and other asphalt surfaces. Forms a durable, flexible and waterproof seal. Resists gas, oil, grease and salt. Exterior use.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
18020	10.1 OZ	BLACK	18017	14.51	12	8"x6"x12"	0.33	8	108

DAP® Blacktop Asphalt VOC-Compliant Filler & Sealer

Asphalt-based, low solvent formulation for the quick and easy repair of cracks in asphalt surfaces. Perfect for playgrounds, driveways, pavement and parking lots. Provides a durable, waterproof, elastic seal. Repairs are ready for traffic in 24 hours. Textured for a professional looking finish. Resists gas, oil, grease and salt. Exterior use.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
27065	10.1 OZ	TEXTURED BLACK	27065	15.00	12	8"x6"x12"	0.33	7	108

DAP® Roof Asphalt Filler & Sealer

High performance, asphalt-based sealant for sealing roof gaps and joints, spotting shingles and repairing minor roof leaks. Forms a durable, flexible, weather resistant and waterproof seal. Can be used for both wet and dry applications. Will not run or bubble. Exterior use.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
18268	10.1 OZ	BLACK	18270	14.51	12	8"x6"x12"	0.33	7	108



DAP® Clear Flexible Sealant

High performance, elastomeric clear sealant. Excellent adhesion even on damp surfaces. Stays crystal clear and flexible. Excellent UV resistance. Cured sealant is mildew resistant. Paintable. Interior/exterior use.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
18384	10.1 OZ	CRYSTAL CLEAR	18376	9.25	12	8"x6"x12"	0.33	6	105

DAP® SEAL 'N PEEL® Removable Weatherstrip Sealant

Unique, removable weatherstrip sealant to seasonally seal drafty windows, doors, air conditioners, vents or fans. Saves energy and reduces utility costs. Provides a temporary waterproof and weatherproof seal. Peels away easily when removal is desired. Won't damage painted surfaces. Interior/exterior use.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
18351	10.1 OZ	CLEAR	18324	9.27	12	8"x6"x12"	0.33	7	105



DAP® BLOCKADE®
Fire-Rated High Performance
Intumescent Acrylic Latex
Sealant

Meets ASTM E814/UL 1479 Specifications. Intumescent product expansion fills voids created by combustible materials burned during a fire. Treats general firestopping applications for combustible and non-combustible penetrations. Excellent adhesion to unprimed surfaces. Red color for easy inspection.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
18858	10.1 OZ	RED	18858	12.25	12	8"x6"x12"	0.33	7	132

DAP® Fire Stop
Fire-Rated
Silicone Sealant

Meets ASTM E814/UL 1479 and UL 2079 Specifications. Classified for sealing fire-rated non-combustible service penetrations and construction joints in horizontal and vertical fire separations. Elastomeric—capable of ±25% dynamic joint movement.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
18806	10.1 OZ	LIMESTONE GRAY	18806	12.75	12	8"x6"x12"	0.33	8	132

DAP® High Heat Mortar
Fire-Resistant Mortar

A non-combustible silicate cement for applications in wood frame construction where an ASTM E136 sealant is required. Can also be used for patching and sealing around fireplaces and wood-burning stoves. Withstands temperatures up to 2000°F, sets rock hard when fired. Easy water clean-up.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
18854	10 OZ	BLACK	18854	15.60	12	8"x6"x12"	0.33	9	102

DAP® Fireblock Foam
Polyurethane Foam Sealant

Quickly fill and seal large gaps around vents, pipes, ducts and wires and at wall-to-floor or ceiling-to-floor joints. Evaluated per ICC-ES Report ESR-1868. For use in Type V residential construction, the foam is bright orange for easy code identification and expands 2-1/2 to 3 times its dispensed size. Just one can of this expanding foam yields up to fifteen large caulk tubes.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
44242	12 OZ	ORANGE	44242	10.00	9	9.12"x9.12"x9.25"	0.45	9	100



**DAPtex® Plus
Multi-Purpose
Foam Sealant**

Designed to meet the tough standards demanded for professional window and door installations while effectively filling and sealing large cracks, gaps and voids. Unlike polyurethane foams, DAPtex® Plus will not overexpand, is toolable, moldable and cleans up easily with water. Remains soft and flexible when dry so it will not bow, buckle or distort frames. The innovative latex polymer foam technology provides water resistance and is paintable with latex paints once cured. Helps reduce energy loss as well as pest infiltration. Ideal for sealing air leaks to improve energy efficiency and reduce heating and cooling costs. Non-clogging, reusable applicator. Interior/exterior use.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
18836	12 OZ	WHITE	18836	13.14	12	10.75"x8.25"x8.5"	0.44	5	90

**DAP® KWIK FOAM®
Polyurethane Insulating
Foam Sealant**

A one-part, moisture-curing polyurethane foam sealant that expands to fill and seal large cracks, gaps and cavities. Stops air, moisture and pest infiltration. Will not shrink or degrade. Reusable for up to 30 days unlike standard one-time use polyurethane foams. Waterproof. Contains a flame retardant. Interior/exterior use.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
18230	12 OZ	TAN	18230	13.10	12	12"x9.25"x8.5"	0.55	1	75
18232	24 OZ	TAN	18232	23.50	12	11.75"x9.5"x11.75"	0.76	5	48



DAP® 3.0™ Window, Door, Trim & Siding High Performance Sealant

DAP® 3.0™ Window, Door, Trim & Siding High Performance Sealant is ideal for sealing windows, door frames, corner joints, siding, trim, butt joints, baseboards, molding, pipes, ducts and vents. It is paintable in 30 minutes to help complete the job faster and save time. In addition, DAP® 3.0™ is 100% waterproof and is water resistant in 30 minutes which reduces the risk of ruining the caulk job by getting it wet too early from incidental rain or water contact. For exterior projects, you can seal up gaps and cracks just 30 minutes before rain is forecasted. Also, DAP® 3.0™ offers extreme temperature use so it can be applied in temperatures ranging from 20°F to 120°F. Lifetime Guarantee. Interior/exterior use. Meets ASTM C920.



Table with 10 columns: Case Code, Size, Color, Product Code, Case Weight (lbs.), Case Pack, Case Dimensions LxWxH, Case Volume (cu.ft.), UPC Check Digit, Cases per Pallet. Rows include 18360 (White) and 18362 (Crystal Clear).

DAP® SILICONE PLUS™ Premium Window & Door 100% Silicone Rubber Sealant

Premium quality, 100% silicone rubber sealant that provides outstanding durability and flexibility for a long-lasting waterproof seal that won't shrink or crack. This one-component, neutral-cure sealant is low in odor and cures to a tough rubbery solid upon exposure to moisture in the air. Provides outstanding adhesion to a wide variety of surfaces such as PVC, vinyl siding and painted wood. Cured sealant is mold and mildew resistant. Interior/exterior use. Backed by a Lifetime Guarantee. Meets ASTM C920 Specification, Class 25, Uses G, A and M.



Table with 10 columns: Case Code, Size, Color, Product Code, Case Weight (lbs.), Case Pack, Case Dimensions LxWxH, Case Volume (cu.ft.), UPC Check Digit, Cases per Pallet. Rows include 08771 (Clear) and 08780 (White).

DAP® All-Purpose 100% Silicone Rubber Sealant

100% silicone rubber sealant provides excellent durability, flexibility and adhesion for a long-lasting, waterproof seal. Resists cracking, crumbling and chalking. Cured sealant is mildew resistant. Interior/exterior use. Meets ASTM C920, Specification C719, Class 25.



Table with 10 columns: Case Code, Size, Color, Product Code, Case Weight (lbs.), Case Pack, Case Dimensions LxWxH, Case Volume (cu.ft.), UPC Check Digit, Cases per Pallet. Rows include 00683 (White), 00684 (Clear), 08646 (White), 08641 (Clear), 08642 (Black), 08643 (Aluminum), 08647 (Bronze), and 08649 (Almond).



DAP® 3.0™ Kitchen, Bath & Plumbing High Performance Sealant

DAP® 3.0™ Advanced Kitchen and DAP® 3.0™ Kitchen, Bath and Plumbing High Performance Sealant is ideal for sealing tubs, showers, sinks, backsplashes, counter tops, toilets and fixtures. It offers 10-year mold resistance and is specially formulated with Microban® Antimicrobial Product Protection to fight the growth of stain and odor-causing mold and mildew on the sealant. Safe for granite and marble. The sealant is easier to clean and stays cleaner between cleanings. DAP® 3.0™ Kitchen, Bath & Plumbing High Performance Sealant is 100% waterproof and is water resistant in 30 minutes. DAP® 3.0™ gets the room back in use quicker and also reduces the risk of ruining the caulk job by getting it wet too early. Lifetime Guarantee.



Table with 10 columns: Case Code, Size, Color, Product Code, Case Weight (lbs.), Case Pack, Case Dimensions LxWxH, Case Volume (cu.ft.), UPC Check Digit, Cases per Pallet. Rows include 00790 (9.0 OZ GLOSS WHITE) and 00795 (9.0 OZ CRYSTAL CLEAR).

DAP® SILICONE PLUS™ Premium Kitchen & Bath 100% Silicone Rubber Sealant

Premium quality, 100% silicone rubber sealant that provides outstanding durability and flexibility for a long-lasting waterproof seal that won't shrink or crack. This one-component, neutral cure sealant is low in odor and cures to a tough rubbery solid upon exposure to moisture in the air. Provides outstanding adhesion to a wide variety of surfaces such as ceramic tile, glass, porcelain and PVC. Cured sealant is mold and mildew resistant. Backed by a Lifetime Guarantee. Meets ASTM C920 Specification, Class 25, Uses G, A and M.



Table with 10 columns: Case Code, Size, Color, Product Code, Case Weight (lbs.), Case Pack, Case Dimensions LxWxH, Case Volume (cu.ft.), UPC Check Digit, Cases per Pallet. Rows include 08781 (10.1 OZ CLEAR), 08770 (10.1 OZ WHITE), and 08785 (10.1 OZ ALMOND).

DAP® Kitchen & Bath 100% Silicone Rubber Sealant

100% silicone rubber sealant provides excellent durability, flexibility and adhesion for a long-lasting, waterproof seal around non-porous surfaces such as ceramic tile and plumbing fixtures. Cured sealant is mildew resistant.



Table with 10 columns: Case Code, Size, Color, Product Code, Case Weight (lbs.), Case Pack, Case Dimensions LxWxH, Case Volume (cu.ft.), UPC Check Digit, Cases per Pallet. Rows include 00680 (2.8 OZ WHITE), 08640 (10.1 OZ WHITE), and 08648 (10.1 OZ CLEAR).



**DAP® Commercial Kitchen
100% Silicone**

DAP® Commercial Kitchen Silicone is an NSF certified product suitable for food-zone areas in commercial and industrial kitchens. This 100% silicone product is 100% waterproof, has a wide temperature range of -75°F to 350°F (intermittent temperatures up to 400°F). Meets FDA Reg 21, CFR 177.2600 and is certified by NSF/ANSI Standard 51.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
08656	9.8 OZ	WHITE	08656	9.8	12	8"x6"x12"	0.33	2	108
08658	9.8 OZ	CLEAR	08658	9.8	12	8"x6"x12"	0.33	6	108
08660	9.8 OZ	STAINLESS STEEL	08660	9.8	12	8"x6"x12"	0.33	9	108



DAP® 3.0™ Self-Leveling Concrete & Masonry High Performance Sealant

Advanced self-leveling concrete and mortar sealant that requires no tooling, making it ideal for filling cracks and gaps in horizontal surfaces. Withstands foot and vehicle traffic after fully cured. It can be applied in all weather and below freezing temperature applications. It won't crack or shrink and provides excellent adhesion, flexibility and durability for a permanent waterproof seal. It can be exposed to water and moisture after only three hours without washing out rather than the 24-36 hour waiting period other caulks and sealants may require. It is paintable, low odor and VOC compliant. Backed by a Lifetime Guarantee. Interior/exterior use.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
18370	9.0 OZ	GRAY	18370	13.12	12	8"x6"x12"	0.33	4	108

DAP® SILICONE PLUS™ Premium Concrete & Masonry 100% Silicone Rubber Sealant

Premium quality, 100% silicone rubber sealant that provides outstanding durability and flexibility for a long-lasting waterproof seal that won't shrink or crack. This one-component, neutral cure sealant is low in odor and cures to a tough rubbery solid upon exposure to moisture in the air. Provides outstanding adhesion to concrete, masonry, brick, ceramic tile, plastic and wood. Cured sealant is mold and mildew resistant. Backed by a Lifetime Guarantee. Interior/exterior use. Meets ASTM Specification C920, Class 25, Type S, Grade NS.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
08675	10.1 OZ	GRAY	08675	11.96	12	8"x6"x12"	0.33	3	108



DAP® SIDE WINDER®
Advanced Siding & Window Sealant

Advanced polymer formula siding and window sealant delivers excellent performance on vinyl, fiber cement, aluminum, wood siding and windows. Provides maximum flexibility. Wet weather and low temperature application. Does not shrink and has virtually no VOC's (<1%). Low odor. Paintable. Interior/exterior use. Meets ASTM Specification C920.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
00801	10.1 OZ	WHITE	00801	13.00	12	8"x 6"x 12"	0.33	4	108
00804	10.1 OZ	CLAY	00804	13.75	12	8"x 6"x 12"	0.33	5	108
00807	10.1 OZ	LIGHT GRAY	00807	13.75	12	8"x 6"x 12"	0.33	6	108
00810	10.1 OZ	TAN	00810	13.75	12	8"x 6"x 12"	0.33	6	108
00813	10.1 OZ	ALMOND	00813	13.75	12	8"x 6"x 12"	0.33	7	108
00823	10.1 OZ	CEDAR	00823	13.75	12	8"x 6"x 12"	0.33	6	108
00835	10.1 OZ	MEDIUM GRAY	00835	13.75	12	8"x 6"x 12"	0.33	9	108
00816	10.1 OZ	CLEAR	00816	9.25	12	8"x 6"x 12"	0.33	8	108

DAP® SIDE WINDER®
Crystal Clear Siding & Window Sealant

Crystal clear siding and window sealant delivers excellent performance on vinyl, fiber cement, aluminum and wood siding. Provides maximum flexibility. Wet weather and low temperature application. Paintable. Interior/exterior use. Meets the performance characteristics of ASTM Specification C920.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
00816	10.1 OZ	CRYSTAL CLEAR	00816	9.25	12	8"x 6"x 12"	0.33	8	108



**DAP® All-Purpose
100% Silicone Adhesive
Sealant**

Long-lasting, 100% silicone rubber is ideal for quick household repairs and projects. Forms a strong, waterproof seal. Won't shrink or crack. Stays flexible. Safe for incidental food contact. Dishwasher and microwave safe. Also ideal for building or repairing aquariums. Harmless to fresh and saltwater fish when cured.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
00688	2.8 OZ	CLEAR	00688	3.30	12	8.5"x6.5"x8.5"	0.27	1	160

**DAP® Auto/Marine
100% RTV Silicone
Sealant**

Long-lasting, 100% RTV silicone rubber seals and bonds for automotive and marine maintenance and repair applications. Forms a strong waterproof and weatherproof seal. Stays flexible. Won't shrink or crack. Resists vibration, expansion and contraction. Endures sunlight and withstands saltwater.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
00694	2.8 OZ	CLEAR	00694	3.40	12	8.5"x6.5"x8.5"	0.27	2	160

**DAP® Gasket
100% RTV Silicone
Sealant**

Easily forms 100% RTV silicone rubber gaskets for mechanical repair and household use. Forms a durable, waterproof seal. Stays flexible. Won't crack, crumble or dry out. Withstands extreme temperatures and pressure. Unaffected by vibration. Resistant to oil, grease and fuels. Requires no mixing.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
00686	2.8 OZ	BLACK	00686	3.30	12	8.5"x6.5"x8.5"	0.27	7	160



**DAP® CAULK-BE-GONE®
Caulk Remover**

Specially formulated gel softens many types of latex caulks and sealants for easy removal. Fast-acting formula works in as little as two hours. Has a fresh scent and will not harm most surfaces. Interior/exterior use.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
18026	5.5 OZ	GREEN	18025	5.21	12	9.5"x7.25"x4.25"	0.17	3	240

**DAP® PRO Caulk™
4-piece
Caulking Tool Kit**

The easy, no-mess way to a perfect, professional seal in seconds. Creates a perfect-looking seal every time – any edge, any corner, any joint – while reducing the amount of wasted caulk, sealant or compound. The Tool Kit includes three unique tools that offer a variety of sealing edge sizes and shapes: a tool for smoothing larger joints, a tool for smaller joints and grouting tile and a mini tool for hard-to-reach places. Plus, there is a bonus caulk removal tool. The tools are made of easy-to-clean Duraflex™ and can be used time and time again. The tools can be used indoors or out, on just about every caulking and sealing project.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
09125	1 EA	BLUE	09125	1.20	4	5.5"x4.75"x11"	0.17	2	224

**DAP CAP™
Caulk Finishing Tool**

Two tools in one. Smooths and finishes bead of caulk or sealant easily for a professional-looking appearance. Works with all types of caulks and sealants. Reseals any cartridge for storage and reuse.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
18570	1 EA	YELLOW	18570	0.82	12	10.5"x4.5"x10.5"	0.29	8	99



DAP Products Inc.

2400 Boston Street, Suite 200
Baltimore, MD 21224
(800) 543-3840
www.dap.com

'33', '1012', 2000, 4000, 7000, Alex, Alex Fast Dry, Alex Plus, Beats The Nail, the Black Band, Blend Stick, Blockade, Bondex, Butyl-Flex, Caulk-Be-Gone, CrackShot, DAP, DAPtex Plus, DryDex, Dynaflex 230, Elastopatch, Fast 'N Final, Kwik Foam, Kwik Seal, Kwik Seal Plus, Patch Stick, Painter's Putty '53', Partial Putty Knife, Plastic Wood, Presto Patch, Project Solutions, Quick Plug, Rely-On, Seal 'N Peel, SIDE Winder, SmartBond, StrongStik, the Putty-Knife Logo, Weldwood and You'll find us in all the right places. are registered trademarks of DAP Brands Company.

3.0™, BlueStik™, CONTACT STIK™, DAP CAP™, Primer 920™, Wood Finish Repair Kit™ and Wood Swell & Lock™ are trademarks of DAP Brands Company.

Webpatch™ 90 is a trademark of Bostik Findley Inc., Wauwatosa, WI.

Pro Caulk is a trademark of National Express Inc.

MICROBAN® and the MICROBAN symbol are registered trademarks of the Microban Products Company, Huntersville, NC.

7040 (09/14)